



YSHIELD® V4A03 | Stainless steel mesh | Width 90 cm | 1 meter

Stainless steel mesh from corrosion-resistant V4A as with maximum shielding for drywall constructions or as flyscreen. 50 dB. Interior and exterior. Width 90 cm.



Properties

V4A03 is an extremely fine woven, **noncorrosive stainless-steel gauze** for the protection against high-frequency radiation (HF) and low-frequency electric fields (LF). **V4A (AISI 316) is resistant against water, water vapor, air humidity, mild acids and in coastal areas against salty seawater!**

Application

Typical application due to the thin filaments especially as flyscreen. In comparison to V4A10, due to the smaller mesh width, the shielding attenuation is better at high frequencies. Further application in **roof areas**, at **drywall constructions**, **loosely laid**, etc.

Processing

In case processing as flyscreen, the application is identical to that of a regular flyscreen in commercial tent frames. Under the floor covering (laminat, parquet, PVC coating, etc.) the V4A03 is being fixed with the adhesive used for the floor covering. For drywall construction and in roof area the mesh elements can be bolt or stapled together. **The rule is:** Always overlap the single elements at least 5 cm. For grounding use the perforated stainless steel tape ELB by screwing it right across the elements into the surface.

Attenuation | Grounding

- This product shields **high frequency electromagnetic fields** (HF). The indicated dB-values apply to 1 GHz, view chart for other frequencies. Expert reports ranging from 40/600 MHz to 40 GHz according to standards ASTM D4935-10 or IEEE Std 299-2006, view report above.
- This product with an electrically conductive surface shields **low-frequency alternating electric fields** (LF). For this purpose a **grounding is necessary**, i.e. an integration into the functional-equipotential bonding (FEB), please find suitable grounding accessories under "Grounding".

Technical data

- **Width: 90 cm**
- **Length: 25 m roll / by the meter**
- **Attenuation: 50 dB**, two-layer 65 dB
- Mesh width: 0.3 mm
- Wire diameter: 0.08 mm
- Material thickness: 0.16 mm
- Open area: 54 %
- Weight: 200 g/m².
- Color: Silver.
- Fire-proof material, A1 according DIN 4102:1994.
- Surface conductivity: 0.03 Ohm (square resistance)